



GRATING PACIFIC

PERF-O GRIP® SAFETY GRATING STAIR TREADS



Widths	Depths	Material
2-Hole - 5" 3-Hole - 7" 5-Hole - 10" 6-Hole - 12"	1-1/2" or 2" Channel Heights	Pre-galvanized Carbon Steel, 13 ga. or 11 ga.

* 2" Channel Height 0.125" Aluminum 5052-H32

Perf-O Grip Recommended Sizes & Spans

Span in.	Material / Gauge	Channel Depth in.	Catalog Number	Width
Up to 30"	Steel 13 ga.	1-1/2"	T-P21513	5"
			T-P31513	7"
			T-P51513	10"
			T-P61513	12"
31" to 48"	Steel 11 ga.	2"	T-P22011	5"
			T-P32011	7"
			T-P52011	10"
			T-P62011	12"
Up to 42"	Alum. .125	2"	T-P220.125-A	5"
			T-P320.125-A	7"
			T-P520.125-A	10"
			T-P620.125-A	12"

*Intermediate supports recommended for all treads spanning greater than 48 inches (42 inches for aluminum treads).

Perf-O Grip Stair Tread Widths

Product Width	A	B	C	D
2-Hole 5"	4-15/16"	1-1/2"	3/4"	2"
3-Hole 7"	6-15/16"	1-1/2"	3/4"	4"
5-Hole 10"	9-15/16"	1-1/2"	3/4"	7"
6-Hole 12"	11-15/16"	1-1/2"	3/4"	9"

