



# GRATING PACIFIC

## 15 SPACE (15/16") ALUMINUM GRATING LOAD TABLE

Use this table when evaluating spans and loads of the following types of aluminum grating:

**15-SG-4, 15-SG-2, 15-SGI-4, 15-SGI-2, 15-SGF-4, 15-SGF-2, 15-ADT-4, 15-ADT-2**

Bearing Bar Size (inches)	Approx. Weight psf *	Max. Ped. Span**	Sec. Prop.*** Sx in <sup>3</sup> Ix in <sup>4</sup>	Unsupported Span									
				2'-0	2'-6	3'-0	3'-6	4'-0	4'-6	5'-0	5'-6	6'-0	6'-6
3/4 x 3/16	2.4	3'-1"	0.225 0.084	U 450	288	200	147	113					
3/4" I-Bar	2.0			D 0.192	0.300	0.432	0.588	0.768					
1 x 1/8	2.1	3'-6"	0.267 0.133	C 450	360	300	257	225					
				D 0.154	0.240	0.346	0.470	0.614					
1 x 3/16	3.1	3'-10"	0.400 0.200	U 533	341	237	174	133	105				
1" I-Bar	2.5			D 0.144	0.225	0.324	0.441	0.576	0.729				
1-1/4 x 1/8	2.6	4'-1"	0.417 0.260	C 533	427	356	305	267	237				
				D 0.115	0.180	0.259	0.353	0.461	0.583				
1-1/4 x 3/16	3.8	4'-7"	0.625 0.391	U 800	512	356	261	200	158				
1-1/4" I-Bar	2.9			D 0.144	0.225	0.324	0.441	0.576	0.729				
1-1/2 x 1/8	3.1	4'-8"	0.600 0.450	C 800	640	533	457	400	356				
				D 0.115	0.180	0.259	0.353	0.461	0.583				
1-1/2 x 3/16	4.5	5'-3"	0.900 0.675	U 1,250	800	556	408	313	247	200	165	139	
1-1/2" I-Bar	3.4			D 0.115	0.180	0.259	0.353	0.461	0.583	0.720	0.871	1.037	
1-3/4 x 1/8	3.6	5'-4"	0.817 0.715	C 1,250	1,000	833	714	625	556	500	455	417	
				D 0.092	0.144	0.207	0.282	0.369	0.467	0.576	0.697	0.829	
1-3/4 x 3/16	5.3	5'-10"	1.225 1.072	U 1,800	1,152	800	588	450	356	288	238	200	170
1-3/4" I-Bar	3.8			D 0.096	0.150	0.216	0.294	0.384	0.486	0.600	0.726	0.864	1.014
2 x 1/8	4.1	5'-10"	1.067 1.067	C 1,800	1,440	1,200	1,029	900	800	720	655	600	554
				D 0.077	0.120	0.173	0.235	0.307	0.389	0.480	0.581	0.691	0.811
2 x 3/16	6.0	6'-6"	1.600 1.600	U 1,633	1,045	726	533	408	323	261	216	182	155
2" I-Bar	4.3			D 0.082	0.129	0.185	0.252	0.329	0.417	0.514	0.622	0.741	0.869
2-1/4 x 3/16	6.7	7'-1"	2.025 2.278	C 2,450	1,568	1,089	800	613	484	392	324	272	232
2-1/4" I-Bar	4.7			D 0.082	0.129	0.185	0.252	0.329	0.417	0.514	0.622	0.741	0.869
2-1/2 x 3/16	7.4	7'-8"	2.500 3.125	C 2,133	1,365	948	697	533	421	341	282	237	202
2-1/2" I-Bar	5.2			D 0.072	0.113	0.162	0.221	0.288	0.365	0.450	0.545	0.648	0.761

\* Weight per square foot based upon 15-SG-4 grating. Add .30 psf for 2" on center cross bars. \*\* Maximum pedestrian load is defined as a 100# uniform load with deflection ≤ 1/4 inch. (The 1/4" maximum deflection criteria is considered consistent with pedestrian comfort, but may be exceeded for other loading conditions at the discretion of the specifying authority.) \*\*\* Section properties per foot of width.

Note: When gratings with serrated surface are specified, the depth of the grating required for a specific load will be 1/4" greater than that shown in these tables.

### Panel Widths

Grating panels are available from stock in nominal 24" and 36" widths. When considering alternative widths, consult this table to select widths that will maintain uniform "out-to-out" spacing of the bearing bars. Specified widths deviating from this table will be fabricated to size with side banding and the bar spacing on one side of the finished panel will vary from the spacing throughout the remainder of the panel.

Number of Bearing Bars	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Panel Width	1-1/8"	2-1/16"	3"	3-15/16"	4-7/8"	5-13/16"	6-3/4"	7-11/16"	8-5/8"	9-9/16"	10-1/2"	11-7/16"	12-3/8"	13-5/16"	14-1/4"
Number of Bearing Bars	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
Panel Width	15-3/16"	16-1/8"	17-1/16"	18"	18-15/16"	19-7/8"	20-13/16"	21-3/4"	22-11/16"	23-5/8"	24-9/16"	25-1/2"	26-7/16"	27-3/8"	28-5/16"
Number of Bearing Bars	32	33	34	35	36	37	38	39							
Panel Width	29-1/4"	30-3/16"	31-1/8"	32-1/16"	33"	33-15/16"	34-7/8"	35-13/16"							

Panel widths indicated are for gratings with 3/16" thick bearing bars. For 1/8" thick bearing bars deduct 1/16" from the stated values. Add 1/4" to all dimensions for extended cross bars on all aluminum products.

Indicates stock panel widths.